



Without WDR



With WDR

# CYBERVIEW PAN/TILT/ZOOM CAMERAS

*With Wide Dynamic  
Range Technology*

## Specifications



DOM-DSC300SI



TRX-DCK255

Image Pickup Device	1/4" Sony CCD w/ DSP 6 (Hitachi) WDR
Effective Pixels	768 (H) x 494 (V) NTSC
Video Output	1.0 V P-P/75Ω NTSC Composite
Resolution	470 TV Line
Communication	RS232C/RS485 (DVR/PTC201)
Zoom	230X (23x Optical, 10x Digital)
Iris Control	Auto On Board
Illumination	0.01 Lux @ F1.2
Pan/Tilt Travel	360°/100°
Speed Pan/Tilt	300°/90°/Sec
BLC/AGC/WB	Auto
Protocol Support	Pelco D
Signal/Noise Ratio	50dB
Operating Temp.	-14 to +122 degrees F
Power Source	24VAC
Dimensions	8.8x7.4
Weight	6.6 lb

Control	Pan/Tilt/Zoom by 3-Axis Joystick
Product Support	DSC300Si, DSC300Se
Communication	RS-485 (422)
Communication Speed	9600bps, N, 8, 1
Connection	Modular through enclosed junction box
Operating Distance	5000' with shielded TP cable
Power	9VDC 500mA 6W
Operating Temp	0 to +40 degrees C
Dimensions	337(W) x 83(H) x 179.2(D) mm
Weight	6.9 lb

