



# DOM-DOH240SI CYBERVIEW SYSTEMS SPEED DOME CAMERA

**230X Zoom,  
True Day & Night, 0.0007Lux**

**INDOOR**

## Specifications

Signal System	NTSC
Image Sensor	1/4" Sony HAD CCD
Effective Pixels	768(H) x 494(V)
Horizontal Resolution	Color : 520 TVL(Min) / B/W : 570TVL(Min)
Lens	23x Optical zoom, f=3.84-88.4mm
Digital Zoom	10x (Total zoom 230x)
Angle of View	H : 52.2° (W) to 2.36° (T), V : 40.252° (W) to 1.78° (T)
Min. Illumination	0.7 Lux@F1.6 (Normal Color Mode) 0.1 Lux@F1.6 (B/W Mode) 0.0007 Lux@F1.6 (Sens-up Mode)
Luminance S/N Ratio	More than 50dB (AGC off)
Viedo Output	1 Vp-p Composite video output 75Ω
Focus Mode	Auto / Manual / Oneshot
Back Light	Off / Low / Middle / High
DIS	On / Off Selectable
SSNR	Off / Low / Middle / High
Shutter Speed	1/60-1/120,000 sec
White Balance	Indoor / Outdoor
Alarm In/Out	4 Inputs / 1 Relay Output
Pan/Tilt Angle	360° Endless / 92°
Pan Speed	0.1° ~ 180° / sec (64 Levels)
Preset Point	250 Presets
Preset Speed	Max 180° / sec (64 Levels)
Communication System	RS-485 / 422
Storage Temperature	-5°C ~ 60°C
OSD	Built-in
Operating Humidity	Less than 90%RH
Operating Temperature	-10°C ~ 50°C (-14°F ~ 122°F)
Dimensions	188.7mm(Diameter) x 216.9mm(Height)
Weight	About 3.1Kg (Without adaptor)
Construction	ABS body, Clear vandal bubble (PC)
Power Consumption	18W (Max)
Power Supply	AC24V, 60/50 Hz

## Features

- 410K Pixel, 1/4" SONY Super HAD CCD
- Horizontal resolution : 520 TVL(Color) 570TVL(B/W)
- 23x Auto focus Optical Zoom, 10x Digital Zoom
- Day & Night IR Cut Filter
- Digital Slow Shutter (Min. illumination 0.0007Lux)
- Digital image stabilizer(DIS)
- Auto Flip (Automatically 180° Turning)
- A variety of surveillance with Swing(2), Presets(250), Group(12), Tour, Trace, Spiral, Alarm (4in/10ut)
- Indoor Vandal Resistance
- Protection for Low Voltage

CyberView  
Systems



CyberView  
Systems

YOUR PEACE OF MIND STARTS HERE.



# DOM-DOH240SI CYBERVIEW SYSTEMS SPEED DOME CAMERA

**230X Zoom,  
True Day & Night, 0.0007Lux**

**INDOOR**

## Specifications

Signal System	NTSC
Image Sensor	1/4" Sony HAD CCD
Effective Pixels	768(H) x 494(V)
Horizontal Resolution	Color : 520 TVL(Min) / B/W : 570TVL(Min)
Lens	23x Optical zoom, f=3.84-88.4mm
Digital Zoom	10x (Total zoom 230x)
Angle of View	H : 52.2° (W) to 2.36° (T), V : 40.252° (W) to 1.78° (T)
Min. Illumination	0.7 Lux@F1.6 (Normal Color Mode) 0.1 Lux@F1.6 (B/W Mode) 0.0007 Lux@F1.6 (Sens-up Mode)
Luminance S/N Ratio	More than 50dB (AGC off)
Viedo Output	1 Vp-p Composite video output 75Ω
Focus Mode	Auto / Manual / Oneshot
Back Light	Off / Low / Middle / High
DIS	On / Off Selectable
SSNR	Off / Low / Middle / High
Shutter Speed	1/60-1/120,000 sec
White Balance	Indoor / Outdoor
Alarm In/Out	4 Inputs / 1 Relay Output
Pan/Tilt Angle	360° Endless / 92°
Pan Speed	0.1° ~ 180° / sec (64 Levels)
Preset Point	250 Presets
Preset Speed	Max 180° / sec (64 Levels)
Communication System	RS-485 / 422
Storage Temperature	-5°C ~ 60°C
OSD	Built-in
Operating Humidity	Less than 90%RH
Operating Temperature	-10°C ~ 50°C (-14°F ~ 122°F)
Dimensions	188.7mm(Diameter) x 216.9mm(Height)
Weight	About 3.1Kg (Without adaptor)
Construction	ABS body, Clear vandal bubble (PC)
Power Consumption	18W (Max)
Power Supply	AC24V, 60/50 Hz

## Features

- 410K Pixel, 1/4" SONY Super HAD CCD
- Horizontal resolution : 520 TVL(Color) 570TVL(B/W)
- 23x Auto focus Optical Zoom, 10x Digital Zoom
- Day & Night IR Cut Filter
- Digital Slow Shutter (Min. illumination 0.0007Lux)
- Digital image stabilizer(DIS)
- Auto Flip (Automatically 180° Turning)
- A variety of surveillance with Swing(2), Presets(250), Group(12), Tour, Trace, Spiral, Alarm (4in/10ut)
- Indoor Vandal Resistance
- Protection for Low Voltage

toll free (877) 475-5716

toll free fax (877) 723-0513

email [sales@ordermatic.com](mailto:sales@ordermatic.com)

320 S. Bryant Pl., Del City, OK 73115

[www.ordermatic.com](http://www.ordermatic.com)



POINT OF SALE SYSTEMS • INTERACTIVE MENU SYSTEMS • WIRELESS & WIRED COMMUNICATION SYSTEMS • DIGITAL VIDEO SURVEILLANCE