



DOM-DSC2000SI CYBERVIEW SYSTEMS HIGH SPEED DOME CAMERA

**300X Zoom,
True Day & Night, 0.0007Lux**

INDOOR

Specifications

Signal System	NTSC
Image Sensor	1/4" Sony HAD CCD
Effective Pixels	768(H) x 494(V)
Horizontal Resolution	More than 520 TVL, B/W 570 TVL
Lens	30x Optical zoom, f=3.3-99 mm
Digital Zoom	10x (Total zoom 300x)
Angle of View	Approx 58.17° (W), Approx 2.2° (Tele)
Min. Illumination	0.7 Lux, 0.1 Lux(D&N), Min 0.0007Lux(DSS), / F1.6
Luminance S/N Ratio	More than 50dB
Video Output	1 Vp-p Composite video output 75Ω
Focus Mode	Auto / Manual / Oneshot
Back Light	Off / Low / Middle / High
SSNR	Off / Low / Middle / High
Shutter Speed	Auto / 1/120-1/60,000 sec
Sharpness control	Level (0-10)
Stabilizer	On/Off
Alarm In/Out	8 Inputs / 2 Relay Output
Pan/Tilt Angle	360° Endless / 92°
Pan Speed	0.1° ~ 240° / sec (64 Levels)
Preset Point	250 Presets
Preset Speed	Max 360° / sec (64 Levels)
Privacy Zones Masking	16 Zones
Operating Temperature	-10°C ~ 50°C (-14°F~122°F)
Communication System	RS-485 / 422
OSD	Built-in
Operating Humidity	Less than 90% RH
Dimensions	155.6mm(Diameter) x 223.6mm(Height)
Weight	About 3.1Kg (Without adaptor)
Construction	ABS body, Clear vandal bubble (PC)
Power Consumption	18W (Max)
Power Supply	AC24V, 60/50 Hz

Features

- 410K Pixel, 1/4" SONY Super HAD CCD
- 30x Auto Focus Optical Zoom, (300x Zoom in total)
- More than 520TV Lines of Horizontal Resolution
- Day & Night (ICR)
- Low Illumination 0.0007 Lux with DSS
- SSNR (Noise Reduction at Low light)
- Back Light Compensation
- Smart Zoom (Speed Control by Zoom Ratio)
- 250 Programmable Preset Positions
- Swing, Group, Trace, Spiral, Auto Flip, Alarm etc.
- 16 Privacy Zone Masking
- Motion Detection Digital Image Stabilizer
- Indoor Vandal Resistance
- Protection for Low Voltage



**CyberView
Systems**

YOUR PEACE OF MIND STARTS HERE. YOUR PEACE OF MIND STARTS HERE. YOUR PEACE OF MIND STARTS HERE.



DOM-DSC2000SI CYBERVIEW SYSTEMS HIGH SPEED DOME CAMERA

**300X Zoom,
True Day & Night, 0.0007Lux**

INDOOR

Specifications

Signal System	NTSC
Image Sensor	1/4" Sony HAD CCD
Effective Pixels	768(H) x 494(V)
Horizontal Resolution	More than 520 TVL, B/W 570 TVL
Lens	30x Optical zoom, f=3.3-99 mm
Digital Zoom	10x (Total zoom 300x)
Angle of View	Approx 58.17° (W), Approx 2.2° (Tele)
Min. Illumination	0.7 Lux, 0.1 Lux(D&N), Min 0.0007Lux(DSS), / F1.6
Luminance S/N Ratio	More than 50dB
Video Output	1 Vp-p Composite video output 75Ω
Focus Mode	Auto / Manual / Oneshot
Back Light	Off / Low / Middle / High
SSNR	Off / Low / Middle / High
Shutter Speed	Auto / 1/120-1/60,000 sec
Sharpness control	Level (0-10)
Stabilizer	On/Off
Alarm In/Out	8 Inputs / 2 Relay Output
Pan/Tilt Angle	360° Endless / 92°
Pan Speed	0.1° ~ 240° / sec (64 Levels)
Preset Point	250 Presets
Preset Speed	Max 360° / sec (64 Levels)
Privacy Zones Masking	16 Zones
Operating Temperature	-10°C ~ 50°C (-14°F~122°F)
Communication System	RS-485 / 422
OSD	Built-in
Operating Humidity	Less than 90% RH
Dimensions	155.6mm(Diameter) x 223.6mm(Height)
Weight	About 3.1Kg (Without adaptor)
Construction	ABS body, Clear vandal bubble (PC)
Power Consumption	18W (Max)
Power Supply	AC24V, 60/50 Hz

Features

- 410K Pixel, 1/4" SONY Super HAD CCD
- 30x Auto Focus Optical Zoom, (300x Zoom in total)
- More than 520TV Lines of Horizontal Resolution
- Day & Night (ICR)
- Low Illumination 0.0007 Lux with DSS
- SSNR (Noise Reduction at Low light)
- Back Light Compensation
- Smart Zoom (Speed Control by Zoom Ratio)
- 250 Programmable Preset Positions
- Swing, Group, Trace, Spiral, Auto Flip, Alarm etc.
- 16 Privacy Zone Masking
- Motion Detection Digital Image Stabilizer
- Indoor Vandal Resistance
- Protection for Low Voltage

toll free (877) 475-5716

toll free fax (877) 723-0513

email sales@ordermatic.com

320 S. Bryant Pl., Del City, OK 73115

www.ordermatic.com



POINT OF SALE SYSTEMS • INTERACTIVE MENU SYSTEMS • WIRELESS & WIRED COMMUNICATION SYSTEMS • DIGITAL VIDEO SURVEILLANCE