



DOM-DMS200SI CYBERVIEW SYSTEMS SPEED DOME CAMERA

*Up To x100 Zoom,
True Day & Night, DSS, DNR*

INDOOR

Specifications

Signal System	NTSC	DOM-DMS200SI
Image Sensor	1/4" Interline Transfer CCD	
Effective Pixels	768(H) x 494(V), 752(H) x 582(V)	
Horizontal Resolution	More than 500 TVL, B/W 570 TVL	
Lens	10x Optical zoom, f=3.8~38mm, F1.8	
Digital Zoom	10x (Total zoom 100x)	
Angle of View	Approx 51.2° (Wide), Approx 5.58° (Tele)	
Min. Illumination	0.0007 Lux@F1.8	
Luminance S/N Ratio	More than 50dB	
Viedo Output	1 Vp-p Composite video output 75Ω	
Focus Mode	Auto / Manual / Oneshot	
Back Light	Off / Low / Middle / High	
SSNR	Off / Low / Middle / High	
Shutter Speed	Auto / 1/28 ~ 1/120,000 sec	
Sharpness Conrol	Level (0-10)	
Motion Detection	On/Off	
Alarm In/Out	4 Inputs / 1 Relay Output	
Pan/Tilt Angle	360° Endless / 92°	
Pan Speed	0.1° ~ 240° / sec (64 Levels)	
Preset Point	250 Presets	
Preset Speed	Max 360° / sec (64 Levels)	
Privacy aones masking	4 Zones	
Communication System	RS-485 / 422	
OSD	Built-in	
Operating Humidity	Less than 90%RH	
Operating Temperature	-10°C ~ 50°C (-14°F ~ 122°F)	
Dimensions	10mm(Diameter) x 138mm(Height)	
Weight	About 0.5Kg	
Construction	PC body, Clear vandal bubble (PC)	

Features

- 410K, 1/4" Interline Transfer Sony CCD
- 10x Optical zoom lens, Auto focus, Auto iris and Zoom tracking
- Horizontal resolution of 500 TVL at color mode and 570 TVL at B/W mode
- Day & Night (ICR)
- Digital noise reduction (DNR)
- Smart zoom
- 250 Preset Positions
- Swing, Group, Spiral, Auto Flip, Alarm
- Privacy Zones Masking

CyberView
Systems



**CyberView
Systems**

YOUR PEACE OF MIND STARTS HERE. YOUR PEACE OF MIND STARTS HERE. YOUR PEACE OF MIND STARTS HERE.